



# Hydraulic Operated Shower Trolley

Hygiene Equipment  
Designed for People



## Generic Specification Text for a Hydraulic Shower Trolley

### Specification for Shower Trolley (hydraulic operated)

- The product is height-adjustable for caregivers ergonomic use and is specifically designed and manufactured for safe in-patient hospital use
- Equipment shall be delivered 100 % assembled and ready for usage
- Hydraulic foot pump operated for raising and lowering to assure hands free operation for caregiver
- Side mounted column design to allow the stretcher to overlap the bed for a safe and easy patient transfer
- Drainage on both foot and head ends for easier positioning
- Easy patient care from both sides
- Foldable side rails for safe patient transfer and caregiver attendance
- Side rails on caregiver's side foldable 180 degrees down for easier access during patient transfer
- Compact base design to allow access under low bed frames
- Floor sling lift transfer capabilities
- Equipped with two brake castors and two straight steering castors for easy patient transport
- Tilt control located at both ends of the trolley for fast "Trendelenburg" position and easy drainage
- Anti-corrosion treatment on all sheet metal parts
- Stainless steel construction on all active movable sheet metal parts
- Mattress can be easily removed for cleaning and is flame retardant
- Shower trolley designed for easy cleaning

### Dimension and load specifications

- |                        |              |                      |               |
|------------------------|--------------|----------------------|---------------|
| • Length:              | Standard     | 1900 +/- 50 mm       | 75 +/- 2 inch |
|                        | Pediatric    | 1600 +/- 50 mm       | 63 +/- 2 inch |
|                        | Extra-long   | 2100 +/- 50 mm       | 83 +/- 2 inch |
| • Width Range:         | 690 - 705 mm | 27 - 27 3/4 inch     |               |
| • Height Range:        | 625 - 925 mm | 24 1/2 - 36 1/2 inch |               |
| • Max. Patient Weight: | 150 kg       | 330 lbs.             |               |

#### Head Office

TR Equipment AB, Sweden  
Phone: +46 140 38 50 60  
info@trequipment.se  
[www.trequipment.com](http://www.trequipment.com)

#### Group Subsidiaries

TR Group Inc, US, Phone: +1 (800) 752 6900  
TR Equipment Ltd, UK, Phone: +44 (0) 844 335 8386  
TRanspoRehaMed GmbH, Germany, Phone: +49 (0) 212 645850-0



TR EQUIPMENT