



Bariatric Shower Trolley

Hygiene Equipment
Designed for People



Generic Tender Specification Bariatric Shower Trolley (270 kg/600 lbs)

Specification for Shower Trolley (bariatric battery operated)

- The product is height-adjustable for the caregivers ergonomic use and is specifically designed and manufactured for safe in-patient hospital use showering both bariatric and taller patients
- Equipment shall be delivered 100 % assembled and ready for use after charging the batteries. Including soft and comfortable flame retardant mattress and head pillow and 1000 mm/39 inch flexible drainage hose
- Hand control operated for raising, lowering and tilting to enable a comfortable and safe working height for the caregiver
- Tilt control in both directions for fast “Trendelenburg” position and easy drainage
- Easy patient care width 180 degrees foldable side rails on both sides for easier access during patient transfer
- Stainless steel foldable side rails that locks into position for safe patient transfer and caregiver attendance
- Side rails must also be foldable inwards when passing through narrow doorways
- Product equipped with bumper wheels on all four corners for wall and doorway protection
- Compact base design to allow access under low bed frames
- The chassis height shall be (140 mm/5^{1/2} inch) to allow mobile sling lift transders
- On board high capacity rechargeable batteries (min. 14 AH) to be charged via main supply
- Magnetic battery charger connection for safety and ease of use
- Mattress can be easily removed for cleaning and is flame retardant
- Foot controlled center locking castor brake system with straight steering
- Anti-corrosion treatment on all sheet metal parts and stainless steel construction on all active movable sheet metal parts
- Shower trolley designed for easy cleaning

Dimension and load specifications

- External Length: max. 2150 mm/85 inch
- External Width: max. 810 mm/32 inch
- Length Patient Work Area min. 1960 mm/77 inch
- Width Patient Working Area min. 640 mm/25^{1/5} inch
- Height Range: 535 - 835 mm/21 - 33 inch
- Max Patient Weight: 270 kg/600 lbs.

Head Office

TR Equipment AB, Sweden
Phone: +46 140 38 50 60
info@trequipment.se
www.trequipment.com

Group Subsidiaries

TR Group Inc, US, Phone: +1 (800) 752 6900
TR Equipment Ltd, UK, Phone: +44 (0) 844 335 8386
TRanspoRehaMed GmbH, Germany, Phone: +49 (0) 212 645850-0



TR EQUIPMENT