



Battery Operated Shower Trolley

Hygiene Equipment
Designed for People



Generic Specification Text for Battery Operated Shower Trolley

Specification for Shower trolley (battery operated)

- The product is height-adjustable for caregivers ergonomic use and is specifically designed and manufactured for safe in-patient hospital use
- Equipment shall be delivered 100 % assembled and ready for use after charging the batteries
- Foot operated for raising and lowering to assure hands free operation for caregiver
- Side mounted column design to allow the stretcher to overlap the bed for a safe and easy patient transfer
- Drainage on both foot and head ends for easier positioning
- Foot operated lifting system for raising and lowering to assure hands free operation for caregiver
- High capacity rechargeable batteries (min. 14 Ah) to be charged via main supply
- Minimum of 80 up-down movements with fully charged batteries with a 100 kg/220 lbs. load
- Magnetic battery charger connection for safety and ease of use
- Easy patient care from both sides
- Foldable side rails for safe patient transfer and caregiver attendance
- Side rails on caregiver's side foldable 180 degrees down for easier access during patient transfer
- Compact base design to allow access under low bed frames
- Floor sling lift transfer capabilities
- Equipped with two brake castors and two straight steering castors for easy patient transport
- Tilt control located at both ends of the trolley for fast "Trendelenburg" position and easy drainage
- Anti-corrosion treatment on all sheet metal parts
- Stainless steel construction on all active movable sheet metal parts
- Mattress can be easily removed for cleaning and is flame retardant
- Shower trolley designed for easy cleaning

Dimension and load specifications

• Length:	Standard	1900 +/- 50 mm	75 +/- 2 inch
	Pediatric	1600 +/- 50 mm	63 +/- 2 inch
	Extra-long	2100 +/- 50 mm	83 +/- 2 inch
• Width Range:	690 - 705 mm	27 - 27 ¾ inch	
• Height Range:	625 - 925 mm	24 ½ - 36 ½ inch	
• Max. Patient Weight:	150 kg	330 lbs.	

Head Office

TR Equipment AB, Sweden
Phone: +46 140 38 50 60
info@trequipment.se
www.trequipment.com

Group Subsidiaries

TR Group Inc, US, Phone: +1 (800) 752 6900
TR Equipment Ltd, UK, Phone: +44 (0) 844 335 8386
TRanspoRehaMed GmbH, Germany, Phone: +49 (0) 212 645850-0



TR EQUIPMENT