



Battery Operated

TR 3200 Shower Trolley

Hygiene Equipment
Designed for People



Generic Specification Text for Battery Operated Shower Trolley

- The product is height-adjustable for caregivers ergonomic use and is specifically designed and manufactured for safe in-patient hospital use
- Equipment shall be delivered with head pillow and drainage as standard
- Equipment shall be delivered 100 % assembled and ready for use after charging the batteries
- Dual lifting columns for trolley bed stability and patient safety
- Offset side mounted column design to allow the stretcher to overlap the bed for a safe and easy patient transfer
- Possibility to easily change designated head end of trolley when needed without any tooling
- Foldable stainless steel side rails for safe patient transfer and caregiver attendance
- Side rails on caregiver's side foldable 180 degrees down for easier access during patient transfer and can be locked upright before moving the trolley from the bed
- "Trendelenburg" tilt possibilities in both directions if needed and for easy drainage
- Mattress can be easily removed for cleaning and is flame retardant
- Shower trolley designed for easy cleaning
- Compact base design to allow access under low bed frames
- Floor sling lift transfer capabilities and 160 mm minimum floor clearance
- Twin castors for extra stability and easier maneuvering
- Two braked castors and Two castors with straight steering for easy patient transport
- High capacity rechargeable batteries (min. 24 V, 7 Ah) to be charged via main supply
- Minimum of 80 up-down movements with fully charged batteries with a 100 kg/220 lbs. load
- Low battery alarm sounds before full depletion of batteries
- Magnetic battery charger connection for safety and ease of use
- Stainless Steel metal parts to assure against potential corrosion

Dimension and load specifications

• Length:	Standard	1900 +/- 50 mm	74.8 +/- 2 inch
	Large	2100 +/- 50 mm	82.7 +/- 2 inch
• Width Range:	Standard	690 - 705 mm	27.2 - 27.8 inch
	Large	770 - 795 mm	30.3 - 31.3 inch
• Height Range:		500 - 900 mm	19.7 - 35.4 inch
• Max. Patient Weight:		200 kg	440 lbs.

Head Office

TR Equipment AB, Sweden
Phone: +46 140 38 50 60
info@trequipment.se
www.trequipment.com

Group Subsidiaries

TR Group Inc, US, Phone: +1 (800) 752 6900
TR Equipment Ltd, UK, Phone: +44 (0) 844 335 8386
TRanspoRehaMed GmbH, Germany, Phone: +49 (0) 212 645850-0



TR EQUIPMENT