



# Height Adjustable Bathtub

Hygiene Equipment  
Designed for People



## Specifications for Height Adjustable Bathtub

### Specifications for basic height adjustable bathtub:

- Electric height adjustable to enable ergonomic working methods for the caregiver.
- Bathtub must include thermostatic mixing valve set at max 43 degrees.
- Bath must be designed to work with a mobile patient lift system to safely manage the entire bathing cycle.
- Bath tub and control panel to be manufactured in fiber glass.
- Control panel with electronic control functions operated by push buttons or touchpad.
- Digital LED thermometer for display of shower and bathtub filling water.
- Bathtub must include adjustable foot support and include patient head pillow.
- Bathtub must include a patient shower with hose and shower handle.

### Specification text to add for **CLEANING** system:

- Integrated disinfection cleaning system.
- Disinfectant storage & Key-locked.

### Specification text to add for **WHIRLPOOL** system:

- Push button controlled whirlpool on/off.
- Single whirlpool outlet that can be quickly fully cleaned and disinfected.
- Water and air adjustment easily adjusted via the air flow control knob.
- Single suction grid.

### Specification text to add for **AUTOFILL** system:

- Autofill with dual preset fill levels to choose from.
- Push button controlled auto fill on/off.
- Lighted display to show activated panel options.

### Dimension and load specifications:

- |                                     |                                     |                                     |
|-------------------------------------|-------------------------------------|-------------------------------------|
| • Operating Height Range (bathtub): | Min: 610 mm/24 inch                 | Max: 940 mm/37 inch                 |
| • Length (bathtub):                 | Min: 2250 mm/88 <sup>1/4</sup> inch | Max: 2350 mm/92 <sup>1/2</sup> inch |
| • Length (inside bathtub)           | Min: 1750 mm/69 inch                |                                     |
| • Width (bathtub):                  | Min: 800 mm/31 <sup>1/2</sup> inch  | Max: 850 mm/33 <sup>1/2</sup> inch  |
| • Weight Limit (patient):           | 150 kg / 330 lbs.                   |                                     |

#### Head Office

TR Equipment AB, Sweden  
Phone: +46 140 38 50 60  
info@trequipment.se  
[www.trequipment.com](http://www.trequipment.com)

#### Group Subsidiaries

TR Group Inc, US, Phone: +1 (800) 752 6900  
TR Equipment Ltd, UK, Phone: +44 (0) 844 335 8386  
TRanspoRehaMed GmbH, Germany, Phone: +49 (0) 212 645850-0



TR EQUIPMENT